

---

### **CASEGOODS (CG) STANDARDS**

- Drawer/door faces to have 1/8" reveal all around
- Doors to use euro hinges
- All edges to be broken and eased
- All drawers to have butt joint construction with lock dowel connection
- All drawers with under mounted, soft close, self close, 3/4" extension glides
- All cases to have 1/4" thick nylon glides or levelers
- Glass to have bumpers for attachment
- 1/2" maple plywood clear coat drawer box components
- Standard glass thickness to be 3/16"
- Standard tempered glass
- Standard stone thickness 2cm or 3cm
- Natural stone is sealed (not impervious to acidic material staining/etching)
- Glass edge detail – 1/16" double beveled edge
- Stone edge detail – eased edges, polished and smooth
- Metal detail – smoothed flush all metal welded joints
- Standard metal material – steel, stainless steel, and brass
- Standard metal finish is powdercoated (or "TNT coating")
- Water based, high performance, industrial urethane clear coat

---

### **SOFTGOODS/UPHOLSTERY (SG) STANDARDS**

- Standard sofa back cushion density #16 foam with 1" dacron
- Standard sofa seat cushions medium density #27 foam with 1" dacron
- Standard sofa pillows medium density #27 with loose dacron
- Sofa base constructed with webbing
- Alligator clips for ganging mechanism
- Fabric seam established by bolt size and pattern
- Upholstery seam established by size of hide for leather
- Standard seaming detail is knife edge
- Loose cushions and pillows with zipper/removable covers, unless buttoned
- Nylon glides

